
Arko 125 S Integrated Overflow

Collection: Elevate Former name: Gyali 125







Freestanding bath – 1700 Integrated overflow, stainless steel overflow slot

Features

- Organic form, high back and smooth contours
- Seamless design
- White sanitary grade acrylic, White Gloss finish
 Excellent heat retention properties
- Excellent heat retention properties
 Adjustable support feet
- Adjustable support feet
- Suits 40mm waste (not supplied)
 Bath has integrated overflow with
- Bath has integrated overflow with polished stainless steel overflow plate

Installation

Refer to installation instructions.

The bath is supplied with four adjustable support feet on the base frame of the bath. Position the bath and use the adjustable feet to level the bath. Leave a 3mm void between the base of the bath and the floor. Use silicone around the base to seal the bath to the floor. Allow a 20mm gap in the silicone seal as a weephole (gap is designed to reveal any plumbing leakage).

Use acetic cured silicone sealant. Do not use epoxy type adhesives.

Order codes

191541

Bath only - Integrated Overflow

Arko 125, 1700 mm

(Old code: SBT-125)

OPTIONAL EXTRA — ORDER SEPARATELY

Bath Installation Kit + Pop-out Waste to suit Integrated Overflow

FlexiWaste Installation Kit with premium Pop-out Bath Waste, with colour options, is available as an optional extra.

Please note: The Pop-out Waste in this kit is suitable for both non-overflow and integrated overflow requirements when used with this kit.

| 192179 | FlexiWaste Bath Installn Kit w Pop-out Waste, IO+NOF, Chrome |
|--------|--|
| 192329 | FlexiWaste Bath Installn Kit w Pop-out Waste, IO+NOF, Brushed Nickel |
| 192332 | FlexiWaste Bath Installn Kit w Pop-out Waste, IO+NOF, Gunmetal |
| 192333 | FlexiWaste Bath Installn Kit w Pop-out Waste, IO+NOF, Brushed Gold |
| 192331 | FlexiWaste Bath Installn Kit w Pop-out Waste, IO+NOF, White Gloss |
| 192458 | FlexiWaste Bath Installn Kit w Pop-out Waste, IO+NOF, White Matte |
| 192330 | FlexiWaste Bath Installn Kit w Pop-out Waste, IO+NOF, Black Matte |

 800

 750

 bath

 Leave a 3mm gap

 between base of

 bath and floor.

 Use silicone to

 seal base of bath

 to floor

 Use silicone to

 seal base of bath

 to floor, leaving a

 20mm weephole.

SEIMA kitchen + laundry + bathroom ware

Bath has integrated overflow.

Please note

- All measurements are in millimetres.
- Dimensions are nominal and subject to normal manufacturing variations.
- Fixing: Use silicone sealant. Do not use epoxy type adhesives.
- Specifications may vary without notice as part of our continuous improvement practices.
 Clean with a damp cloth. Do not use abrasive cleaners, liquids or pastes.



Scan to view bath on our website