Flush Plate 500



Flush Plate for InWall toilets — Pneumatic system

- Pneumatic push button system
- Easy to install and service

Order codes

191804	Flush plate 500 – Chrome	Old code: STO-B500-C
192063	Flush plate 500 – Brushed Nickel	
192181	Flush plate 500 – Gunmetal	
191803	Flush plate 500 – Black matte	Old code: STO-B500-B
192276	Flush plate 500 – White matte	
192064	Flush plate 500 – Brushed Gold	


Product details


MATERIALS ABS plastic base.

Brushed Nickel and Brushed Gold: PVD.

236W x 152H x 8D mm.

INSTALLATION Refer to installation instructions.








Chrome



Black matte




Brushed Nickel (PVD)



White matte



Gunmetal



Brushed Gold (PVD)



seima.com.au

- Installation shall be in accordance with AS/NZS3500.
- All measurements are in millimetres. Height dimensions are to base of pan. Make allowance for bedding.
- Bedding: Pan may be bedded with cement base or using silicone sealant. Fix pan to floor using a sand cement mixture of 3:1 to a depth of 60mm. Do not use lime or fast-drying cement.
- Bracket fixing: The pan should be bedded with silicone sealant and fixed with the brackets supplied.
- Do NOT use epoxy type adhesives.
- Dimensions are nominal and subject to normal ceramic manufacturing variations.
- Specifications may vary without notice as part of our $continuous\ improvement\ practices.$
- Clean with a damp cloth. Do not use abrasive cleaners, liquids or pastes.