Modia Care Floor Mount – 800mm © 🙈





AS1428.1 Accessible

Collection: Elevate

Former name: Modia Care Floor Mount - 800mm









Optional backrest (stainless steel)

Flush Plate 300 — raised flush buttons

Modia Care floor mount toilet suite

- Clean Flush, Easy Care Height
- Choice of grey, blue or white seat
- Stylish minimalist design, sits flat against wall
- Clean Flush rimless pan design for an efficient, powerful flush
- Easy care height
- White vitreous china
- Care toilet seat, available in Blue and White
- Optional stainless steel backrest

PAN AND SEAT

S or P trap

Order codes

Order each item separately.

192419	Modia Care FM pan with GREY seat
191967	Modia Care FM pan with BLUE seat
191968	Modia Care FM pan with WHITE seat
191806 191807	IN-WALL CISTERN C100 inwall cistern, 80 mm thick (suits FM, standard wall installn) C101 inwall cistern, 130 mm thick (suits FM, nib wall installation)
191798	RAISED FLUSH BUTTONS Flush Plate 300 — raised buttons, chrome plated metal
191971	BACKREST Backrest to suit Modia Care toilets, stainless steel

OPTIONAL SETOUT CONNECTOR

X6000016 Connector for setout 75-215 mm (see 'Setout' below)

Product details

FIXING

PAN Wall fac	ed with rimless	pan design.
--------------	-----------------	-------------

MATERIAL White vitreous china.

TRAPS Universal trap, suitable for S or P trap installations.

SEAT Care toilet seat, available in Blue and White. Seats are available

separately as spare parts.

Optional backrest: 32 mm stainless steel, 304 grade, brushed BACKREST

finish, AS1428 compliant.

WELS 4 star rating 4.5/3 litre water saving flush.


Variable 190-280 mm. SETOUT


Optional connector setout range 75-215 mm (code X6000016) Pan may be bedded with cement base or using silicone sealant.


CISTERN Order cistern to suit installation type. Floor mount pan suits in-wall

cisterns C100 and C101


BUTTONS Recommended: Flush Plate 300, raised flush buttons, chrome.








(Optional connector setout range 75-215 mm)







kitchen + laundry + bathroom ware

- Installation shall be in accordance with AS/NZS3500.
- All measurements are in millimetres. Height dimensions are to base of pan. Make allowance for bedding.
- Bedding: Pan may be bedded with cement base or using silicone sealant. Fix pan to floor using a sand cement mixture of 3:1 to a depth of 60mm. Do not use lime or fast-drying cement.
- Bracket fixing: The pan should be bedded with silicone sealant and fixed with the brackets supplied.
- Do NOT use epoxy type adhesives.
- Dimensions are nominal and subject to normal ceramic manufacturing variations.
- Specifications may vary without notice as part of our continuous improvement practices.
- Clean with a damp cloth. Do not use abrasive cleaners. liquids or pastes.