
# Syros 105 G Integrated Overflow

## **Collection: Foundation**









## Freestanding bath – 2 sizes Integrated overflow, slot design Features

### cutures

- Fine rim, elegant super-ellipse design
- Seamless design
- White sanitary grade acrylic, high gloss finish
  Excellent heat retention properties
- Excellent heat retention properties
  Adjustable support feet
- Adjustable support feetSuits 40mm waste (not supplied)
- Approx weight: 1500, 36kg; 1700, 40.4kg
- Bath has integrated overflow, slot design

## Available in 2 sizes

- 1500 mm long
- 1700 mm long

## Installation

Refer to installation instructions.

The bath is supplied with four adjustable support feet on the base frame of the bath. Position the bath and use the adjustable feet to level the bath. Leave a 3mm void between the base of the bath and the floor. Use silicone around the base to seal the bath to the floor. Allow a 20mm gap in the silicone seal as a weephole (gap is designed to reveal any plumbing leakage).

Use acetic cured silicone sealant. Do not use epoxy type adhesives.

## Order codes

## Bath only - Integrated Overflow

192211Syros 105 – Integrated Overflow, 1500 (waste not included)192212Syros 105 – Integrated Overflow, 1700 (waste not included)


## **OPTIONAL EXTRA** — ORDER SEPARATELY

## Bath Installation Kit + Pop-out Waste to suit Integrated Overflow

FlexiWaste Installation Kit with premium Pop-out Bath Waste, with colour options, is available as an optional extra.

Please note: The Pop-out Waste in this kit is suitable for both non-overflow and integrated overflow requirements when used with this kit.

192179FlexiWaste Bath Installn Kit w Pop-out Waste, IO+NOF, Chrome192329FlexiWaste Bath Installn Kit w Pop-out Waste, IO+NOF, Brushed Nickel192332FlexiWaste Bath Installn Kit w Pop-out Waste, IO+NOF, Gunmetal192333FlexiWaste Bath Installn Kit w Pop-out Waste, IO+NOF, Brushed Gold192331FlexiWaste Bath Installn Kit w Pop-out Waste, IO+NOF, White Gloss192458FlexiWaste Bath Installn Kit w Pop-out Waste, IO+NOF, White Matte192330FlexiWaste Bath Installn Kit w Pop-out Waste, IO+NOF, Black Matte



Leave a 3mm gap between base of bath and floor. Use silicone to seal base of bath to floor, leaving a 20mm weephole.

Base has four adjustable support feet.





SEIMA kitchen + laundry + bathroom ware

#### Please note

- All measurements are in millimetres.
- Dimensions are nominal and subject to normal manufacturing variations

740

- Fixing: Use silicone sealant. Do not use epoxy type adhesives.
- Specifications may vary without notice as part of our continuous improvement practices
- Clean with a damp cloth. Do not use abrasive cleaners, liquids or pastes.



Scan to view bath on our website