

Toilet Colour Flush Buttons + Seat Hinge Covers

Former name: Toilet Colour Pack

Now you can choose colour toilet flush buttons and seat hinge covers to match your bathroom design.

Available for Arko, Modia and Limni toilet suites.
Easy to install.



Colour flush buttons

Note: Toilets come with chrome flush buttons and stainless steel seat hinges covers as standard.

Colour buttons and seat hinge covers are extras, fitted in place of the standard items.



Colour seat hinge covers



Available for:

Wall faced toilets:
Arko + Modia + Limni

Floor mount toilets:
Arko + Modia

Wall hung toilets:
Arko + Modia

Order codes

COLOUR FLUSH BUTTONS



Colour Flush Button to suit:

- ARKO Wall Faced toilet suite
- MODIA Wall Faced toilet suite
- LIMNI Wall Faced toilet suite

Colour	Order code
White Matte Fl/btn	192413
Black Matte Fl/btn	191201
Brushed Nickel Fl/btn	191212
Gunmetal Fl/btn	191206
Brushed Gold Fl/btn	191226

COLOUR SEAT HINGE COVERS



Set of 2 Seat Hinge Covers to suit:

- DELUXE toilet seat
- CLASSIC toilet seat

Colour	Order code
White Matte Dlx-Hinge	192414
Black Matte Dlx-Hinge	191234
Brushed Nickel Dlx-Hinge	191236
Gunmetal Dlx-Hinge	191235
Brushed Gold Dlx-Hinge	191233



Set of 2 Seat Hinge Covers to suit:

- SLIM toilet seat

Colour	Order code
White Matte Slim-Hinge	192360
Black Matte Slim-Hinge	191232
Brushed Nickel Slim-Hinge	191216
Gunmetal Slim-Hinge	191210
Brushed Gold Slim-Hinge	191230



Set of 2 Seat Hinge Covers to suit:

- FLAT toilet seat

Colour	Order code
White Matte Flat-Hinge	192360
Black Matte Flat-Hinge	191231
Brushed Nickel Flat-Hinge	191215
Gunmetal Flat-Hinge	191209
Brushed Gold Flat-Hinge	191229

SEIMA

kitchen + laundry + bathroom ware

seima.com.au

Please note

- Installation shall be in accordance with AS/NZS3500.
- All measurements are in millimetres. Height dimensions are to base of pan. Make allowance for bedding.
- Bedding: Pan may be bedded with cement base or using silicone sealant. Fix pan to floor using a sand cement mixture of 3:1 to a depth of 60mm. Do not use lime or fast-drying cement.

- Bracket fixing: The pan should be bedded with silicone sealant and fixed with the brackets supplied.
- Do NOT use epoxy type adhesives.
- Dimensions are nominal and subject to normal ceramic manufacturing variations.
- Specifications may vary without notice as part of our continuous improvement practices.
- Clean with a damp cloth. Do not use abrasive cleaners, liquids or pastes.