Flush Plate 700



















Flush Plate 700 for InWall toilets

- Pneumatic actuation
- Mechanical actuation

Product features

- Available in Pneumatic or Mechanical actuation
- Push button system
- Easy to install and service

Available in 6 finishes

- Brushed Nickel, PVD
- Gunmetal
- Brushed Gold, PVD
- Black Matte
- White Matte
- Chrome

Product details

MATERIALS ABS plastic.

DIMENSIONS 236W x 152H x 8D mm.

INSTALLATION Refer to installation instructions.

Order codes

Flush Plate 700 – Pneumatic actuation

193185	Flush Plate 700, Pneumatic, Brushed Nickel
193184	Flush Plate 700, Pneumatic, Gunmetal
193183	Flush Plate 700, Pneumatic, Brushed Gold
193182	Flush Plate 700, Pneumatic, White Matte
193180	Flush Plate 700, Pneumatic, Black Matte
193181	Flush Plate 700, Pneumatic, Chrome

Flush Plate 700 – Mechanical actuation

193191	Flush Plate 700M, Mechanical, Brushed Nickel
193190	Flush Plate 700M, Mechanical, Gunmetal
193189	Flush Plate 700M, Mechanical, Brushed Gold
193188	Flush Plate 700M, Mechanical, White Matte
193186	Flush Plate 700M, Mechanical, Black Matte
193187	Flush Plate 700M, Mechanical, Chrome

SEIMA

kitchen + laundry + bathroom ware

seima.com.au

Please note

152

- Installation shall be in accordance with AS/NZS3500.
- All measurements are in millimetres. Height dimensions are to base of pan. Make allowance for bedding.
- Bedding: Pan may be bedded with cement base or using silicone sealant. Fix pan to floor using a sand cement mixture of 3:1 to a depth of 60mm. Do not use lime or fast-drying cement.
- Bracket fixing: The pan should be bedded with silicone sealant and fixed with the brackets supplied.
- Do NOT use epoxy type adhesives.
- Dimensions are nominal and subject to normal ceramic manufacturing variations.
- Specifications may vary without notice as part of our continuous improvement practices.
- Clean with a damp cloth. Do not use abrasive cleaners, liquids or pastes.